

Floorcare Chemicals

This guide provides information on how to get the best performance and value from your Jangro range



DILUTION RATES FOR JANGRO FLOORCARE CHEMICAL PRODUCT RANGE



Jangro Wet Look Floor Polish 25% Solids

On a clean, dry, neutral floor, apply two thin coats with clean mop or applicator. Allow each coat to dry. A third coat may be required on old or worn floors.

For best results, maintain with Jangro Perfumed Floor Maintainer.



Jangro High Traffic Floor Polish 21% Solids

On a clean, dry, neutral floor, apply two thin coats with clean mop or applicator. Allow each coat to dry. A third coat may be required on old or worn floors.

For best results, maintain with Jangro Perfumed Floor Maintainer.



Jangro Perfumed Floor Maintainer

Spray cleaning: Dilute 10ml per 500ml cold water in a spray bottle. Spray floor lightly, buff to a shine.

Mopping: Dilute 100ml per 5 litres warm water. Mop floor, when dry, burnish to shine.



Jangro Lemon Floor Gel

Spray cleaning: Dilute 10ml per 500ml of cold water in a spray bottle. Spray floor lightly, buff to shine.

General cleaning: Dilute 100ml per 5 litres of warm water. Mop floor, when dry, burnish to a shine.



Jangro Pine Floor Gel

Spray cleaning: Dilute 10ml per 500ml of cold water in a spray bottle. Spray floor lightly, buff to shine.

General cleaning: Dilute 100ml per 5 litres of warm water. Mop floor, when dry, burnish to a shine.



Jangro Scrubber Dryer Solution

Light soilage: Dilute 50ml per 5 litres of water

Heavy soilage: Dilute 100ml per 5 litres of water

DILUTION RATES FOR JANGRO FLOORCARE CHEMICAL PRODUCT RANGE



Jangro Scrubber Dryer Solution Power

For use with combination machines: Add 1-2% to the solution tank, depending on soiling.
General cleaning: Dilute 100ml per 5 ltrs of hot water. Mop or wipe surface.



Jangro Neutral Floor Cleaner

General cleaning: Dilute 25ml per 5 litres of water. Mop or wipe the surface.
Spray cleaning: Dilute 10ml per 500ml of cold water in a hand spray. Spray floor lightly, buff to a shine.



Jangro Floor Polish Remover

Polish stripping: Dilute 250ml per 5 litres of hot water.
Heavy build up: Dilute 500ml per 5 litres of hot water.

Apply with mop or machine tank. Leave for a few minutes, machine scrub with stripping pad. Remove slurry, rinse with clean water. Neutralise floor before applying polish by adding a solution of 20ml of acetic acid (vinegar) to 5 litres of water and damp mop the surface. Allow to dry.



Jangro Floor Polish Remover Rinse Free

Polish removal with mop: Dilute 800ml per 5 litres warm water. Spread solution generously on floor, leave for 5 mins, agitate with mop, leave for a few mins, not allowing the solution to dry out. Re-agitate with mop and remove completely with mop or suction dryer. Rinse with clean water.

Polish removal with machine: Dilute 100ml per 5 litres of warm water.

Spray stripping: Dilute 25ml per 500ml of cold water in a hand spray. Spray floor lightly and scrub, using pad and high speed machine.



Jangro Floor Polish and Cleaner

Cleaner/Polish: Apply a thin coat and rub lightly with a mop to remove light soilage. Rinse mop and apply second coat.

Polish: Apply a thin coat, allow to dry, apply a second coat and burnish if necessary.

Cleaner: Dilute 500ml per 5 litres of cold water and damp mop floor.

Spray cleaning: Dilute 10ml per 500ml of cold water in a hand spray. Spray floor lightly and buff to a shine.



Jangro Oleo Resinous Floor Seal

Remove existing seal. Ensure floor is clean and dry. Apply undiluted two or three thin coats with seal applicator or a clean soft brush. Allow each coat to dry for 8 hrs. Additional coats can be applied if required. Sanding in between coats is not necessary, but a light sand with a medium grade floor pad will help key the surface if a 3rd or 4th coat is applied.

After the final coat, leave for 12 hrs before subjecting to traffic, 24hrs before cleaning and 7 days before applying emulsion floor polish.

Coverage rate - approx. 30 sq.mtrs for 2 coats.

DILUTION RATES FOR JANGRO FLOORCARE CHEMICAL PRODUCT RANGE



Jangro Polyurethane Floor Seal Water Based

For best results, apply to a clean untreated floor surface.

1. Use undiluted
2. Apply a thin, even coat with a seal applicator or clean mop.
3. Allow to dry for a minimum of 2 hours.
4. Apply a second and third coat allow to dry as first coat

Coverage rate: Approx. 30-40 sq.mtr for 2 coats.



Jangro Polyurethane Floor Seal

Remove existing seal. Ensure floor is clean and dry.

Apply undiluted two or three thin coats with seal applicator or a clean soft brush. Allow each coat to dry for 8 hrs.

Additional coats can be applied if required. Sanding in between coats is not necessary, but a light sand with a medium grade floor pad will help key the surface if a 3rd or 4th coat is applied.

After the final coat, leave for 12 hrs before subjecting to traffic, 24 hrs before cleaning and 7 days before applying emulsion floor polish.

Coverage rate - approx. 30sq. mtrs for 2 coats.



Jangro Acrylic Floor Primer

Use undiluted.

On a clean, dry, neutral floor, apply a thin coat with clean mop or applicator. If the floor is very old and porous, a second coat may be required.



Jangro Extraction Carpet Cleaner (Woolsafe)

A specially formulated cleaner suitable for woven and non-woven carpets of synthetic and natural fibres when used in conjunction with a hot water extraction machine. Also safe and effective for the cleaning of upholstery fabrics especially car seats.

Dilute 60ml per 5 litres of hot water. Ensure detergent spray is not blocked and suction recovery is functioning correctly. Spray and pick up in accordance with manufacturers recommendations. Ensure that as much liquid as possible is extracted from the carpet to speed up drying.

N.B Test a small conspicuous area of the carpet for colour fastness before commencing cleaning.



Jangro Dry-Foam Carpet Cleaner (Woolsafe)

Suitable for use with all types of brush operated carpet machines. Use in accordance with machine manufacturers recommendations.

In general dilute 300ml per 5 litres of warm water for automatic machines.

Dilute 500ml per 5 litres of warm water for hand machines. Apply fluid sparingly, work up to a good lather with brush. Leave to dry. Vacuum thoroughly.

N.B. NOT suitable for use with hot water extraction machine.

DILUTION RATES FOR JANGRO FLOORCARE CHEMICAL PRODUCT RANGE



Jangro Carpet Spot and Stain Remover (Woolsafe)

Dry spots should be agitated before application, taking care not to damage delicate fabrics. Spray onto affected area. Allow time to penetrate.

Absorb the stain by blotting with white paper or extract with a machine.

N.B. Before application always test for colourfastness on an inconspicuous area.



Jangro Traffic Lane Carpet Cleaner

Dilute 50ml to 5 litres of hot water. Ensure detergent spray is not blocked and suction recovery is functioning correctly. Spray and pick up in accordance with machine manufacturers recommendations. Ensure that as much liquid as possible is extracted from the carpet to speed up drying.

For general pre-spraying dilute 500ml to 5 litres of water. For heavily soiled areas pre-spray with 1 litre per 5 litres of warm water then use Extraction carpet Cleaner as normal.

N.B. Test a small inconspicuous area of the carpet for colour fastness before commencing cleaning.



Enviro Floor Gel

Mopping: Dilute 80 ml per 5 litres of hot water. Mop floor, when dry burnish to a shine.

Spray cleaning: Dilute 100ml per 500ml of cold water in a spray bottle. Spray floor lightly and burnish to a shine.



Enviro Floor Maintainer (unperfumed)

Spray cleaning: Dilute 10ml per 500ml cold water in a spray bottle. Spray floor lightly, buff to a shine.

Mopping: Dilute 100ml per 5 litres of warm water. Mop floor, when dry, burnish to a shine.

Dilution guides are also available for the Jangro Housekeeping, Washroom and Kitchen range