



K.1.IMP40N.FCT.0

i-mop 40

Includes standard medium brush, squeegee and rubber wheels.

Batteries



K.1.S.115.1163.357

i-power 14U

battery

K.1.S.115.0142.0

i-charge charger

Tanks



K.1.S.115.1089.2AT

Recovery tank

Replacement recovery water tank.



K.1.S.115.1079.0B

Clean water tank

Replacement clean water tank.



K.1.S.115.1079.2AT

Clean water tank with i-dose

Replacement clean water tank.

Brushes



K.2.S.139.0092.797

Blue brush

0.30mm



K.2.S.139.0092.1

Red brush


0.50mm



K.2.S.139.0092.70

Blue brush

0.15mm



K.2.S.139.0092.592

Blue brush

0.30mm

Traditional pads



K.20.139.0213.0

Black

Very aggressive scrubbing and stripping.



K.20.139.0213.1

Red

Regular buffing and cleaning pad.



K.20.139.0213.2

White

Light buffing & polishing.



K.20.139.0213.64

Green

Aggressive scrubbing pad, unsealed floors.



K.20.139.0213.79

Blue

Heavy cleaning pad, dull or unsealed floors.

Squeegees



K.1.S.139.0341.0

Ez squeegee LTX/PA



K.1.S.139.0341.1

Ez squeegee PMT/PA



K.10.139.1384.2A

FRONT Linatex



K.10.139.1384.3A

FRONT Primothane



K.10.139.3383.21

REAR Linatex



K.10.139.3383.31

REAR Primothane

Rubbers



faster



cleaner



greener



safer



better

Paddriver

Cleaning



K.2.S.139.0214.797

Pad driver

Use in combination with all our pads.



K.1.72.0324.0

Cleaning brush

For i-mop dirt tank.

i-dose



K.120.72.0444.6

i-dose 7 Degrease

Green



K.120.72.0444.111

i-dose 3 Sanitary

Pink



K.120.72.0444.7

i-dose 5 Daily

Blue



K.120.72.0444.0

i-dose 3/5/7

Mixed

Technical specifications i-mop 40



Theoretical performance	1850 m ² – based on i-power 14U (71 minutes runtime) 1400 m ² /h
Practical performance	960 m ²
Brush speed	350 RPM
Brush pressure	without water: 14.3 kg with water: 18 kg (3.5 L)
Operation width	400 mm
Size machine (l x w x h)	1130 x 500 x 290 mm
Weight without batteries & water	12.7 kg
Weight with batteries & water 3Ltr	17.8 kg
Clean water tank	3 L
Recovery tank	4 L
Noise level	Brush only: 64 dB & vac + brush 71 dB
Power source	i-power 14U i-power 20U
Battery spec	i-power 14U: 18.0 V (14 Ah)
Runtime	i-power 14U: 71 minutes * on rough flooring i-power 14U: 81 minutes * (i-power 14) on smooth surfaces
Charger type	100-240 V, 50/60 Hz
Charger	i-charge 5 *

* Batteries and charger can be ordered separately.

wraybros.co.uk